

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 and 34½, T29-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6520)

Set a post, at proper distance, corner of secs. 2, 3, 34 and 35, from which

- A Pine 15" dia., bears N.5°W., 10 lks. dist.
- A B.Oak 12" dia., bears N.30°E., 50 lks. dist.
- A B.Oak 12" dia., bears S.80°E., 35 lks. dist.
- A B.Oak 30" dia., bears S.5°W., 153 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6044-45)

Intersect the point for cor. of secs. 2,3, 34 and 35, located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for xoe. od awxa. 34 and 34½, T29S R7W, with brass cap marked:

T29S:R7W

S34:S34½

1924

from which (the original bearing trees)

- A B.Oak 30" dia., bears N.59°E., 53 lks. dist. (not N.30°E., 50 lks.) marks plain; opened overgrowth shows marks 70 years old.
- A B.Oak 36" dia., bears S.2°E., 153 lks. (not S.5°W.) shows scar of blaze.
- A B.Oak 26" dia., bears S.81°W., 35 lks. dist., (not S.80°E.), overgrowth opened, 70 years old, marks plain.
- A Pine stump hole, bears N.5°W., 10 lks. dist.

New Bearing trees:

- A Fir 12" dia., bears N.51°E., 23 lks. dist., mkd. T29S R7W S34½ BT.
- A Fir 20" dia., bears N.62°W., 42 lks. dist., mkd. T29S R7W S34 BT.

Fd. OK, BLM resurvey by Wofford; Popken and Carlson, Sept. 1974/May 1976 (DCSO records Vol. 39 Page(s) 15812-13) AND BLM resurvey by Jelley & Rogers, 1981 (DCSO records Vol. 42 Page(s) 16424)