

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100137

PRIMARY CORNER DESCRIPTION SE Tsp cor. T30-1 & NE Tsp Cor T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7501)

Set a basalt stone 24x12x10 ins., 18" in the ground for cor. of Tps. 30 and 31 S., R 1 W., mkd. with 6 notches on N., S., and W. faces, from which

A Fir 30" dia., bears S.30°W., 25 lks. dist. mkd. T31S R1W S1 BT.

A Fir 24" dia., bears N.5°W., 27 lks. dist. mkd. T30S R1W S36 BT.

Corner Fd. and Used in GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7516)

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1968 - C.S. File 54/59-47

Found - Corner stone, no marks.

30" D.Fir now 40" stump, S.30°W., 16.5 ft., opened and found scribe.

26" D.Fir now 28" snag, N.2°W., 16.5 ft., opened and found scribe.

Set Brass cap at cor. mkd: County Surveyors Office 1968

R	T 30	S	R
1	S 36		S31 1
W	S 1		E
	T 31	S	

New BTs- 6" Cedar S.60°W., 10.4 ft. scribed T31S R1W S1 CS BT
36" D.Fir N.18°W., 15.2 ft. scribed T30S R1W S36 CS BT.

¼ Cor. to sec. 31 only, T30-1E, is OK and lies North 236.3 ft., both corners on steep West slope.