

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6744)

Set an iron post 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 30 & 31, T30S R1E only, with brass cap marked:

| | |
|------|------|
| T30S | T30S |
| R1W | S 30 |
| S36 | S 31 |
| | R1E |
| | 1923 |

from which

A Fir 34" dia., bears N.44°E., 25 lks. dist. mkd. T30S R1E S30 BT.

A Fir 18" dia., bears S.20°E., 13 lks. dist. mkd. T30S R1E S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1968 - C.S. File 54/59-46

Found - Brass cap, 1923 GLO, pulled out of ground by other blow-down.

18" D.Fir, blow-down, S.20°E., 8.6 ft., opened and found scribe.

34" now 38" D.Fir N.44°E., 16.5 ft. This dist. must be slope dist. to match bearings and other distances.

RESET 1923 GLO brass cap at section corner.

New BT - D.Fir, S.87°E., 30.5 ft. mkd. T30S R1E S31 CS BT.

Cor. lies 236.3 ft. North of ¼ cor. sec. 36 only, T30S R1W.