

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100237

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only; T30-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6680)

Set a basalt stone 20x10x8 ins., 15" in ground for corner of secs. 25 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which
A Fir 18" dia., bears S.64°W., 32 lks. dist. mkd. T30S R1W S36 BT.
A Fir 18" dia., bears N.10°W., 42 lks. dist. mkd. T30S R1W S25 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6744)

The cor. of secs. 25 and 36, which is a basalt stone 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I mark the stone additionally S36 on SW., and S25 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1968 - C.S. File 54/59-49

Found - 18" now 22" D.Fir S.64°W., 21.1 ft. scribe visible "36".
18" now 22" D.Fir N.10°W., 25.7 ft. (Rec. 27.7 ft.) shows good scar.

Old mound of stones at corner, no marks found.
Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
1 S 25 | S30 1
W S 36 | E
1968

Old BTs in good condition, tagged same.
Cor. lies 236.3 ft. South of ¼ cor. to sec. 30 only. (OK)