

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6745)

Set an Iron post 3 ft. long, 2" dia., 27" in the ground for the cor. of secs. 19 and 30 only, with brass cap marked:

T30S	T30S
R1W	S 19
S25	S 30
	R1E
	1923

from which

A Madrona 16" dia., bears N.20°E., 15 lks. dist. mkd. T30S R1E S19 BT.

A Fir 14" dia., bears S.68°E., 37 lks. dist. mkd. T30S R1E S30 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan/Feb. 1968 - C.S. File 54/59-57

Found - 1923 GLO brass cap at sec. cor., properly marked. 14" D.Fir now stump, S.68°E., 24.4 ft., opened for scribe, "¼ S30 BT".

No trace of NE. bearing tree.

No trees in area, cut unit:

24" D.Fir stump, S.81½°E., 23.0 ft., drove ¾" I.Rod in center of stump.

20" D.Fir stump, N.21½°E., 20.2 ft., drove ¾" I.Rod in center of stump.

Cor. lies 236.3 ft. North of ¼ sec. 25 only. Cor. lies approx. 100 ft. South and 70 ft. W. of logging road above high cut bank.