

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only; T30-1W

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6682)

Set a basalt stone 20x12x5 ins., 15" in ground for ¼ sec. corner, marked ¼ on W. face, from which
A Fir 12" dia., bears N.20°E., 11 lks. dist. mkd. ¼ S19 BT
A Fir 20" dia., bears West, 3 lks. dist. mkd. ¼ S24 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6746)

The original ¼ sec. cor., which is a basalt stone, 12x5x5 ins. above ground, firmly set, marked ¼ on W. face. Hereafter this cor. will refer to sec. 24 only.
I mark the ocr. stone ¼ S24 on W. face, from which
A Fir 30" dia., bears S.75°W., 3 lks. dist. mkd. ¼ S24 BT. (Old BT)
A Fir 30" dia., bears N.58°W., 51 lks. dist. mkd. ¼ S24 BT. (New BT)
I obliterate the marks on the old BT in sec. 19.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-114

Found - Stone at corner, no marking.
30" D.Fir, now snag, S.75°W., 2.0 ft., snows scribing "¼ S24".
30" now 36" D.Fir, N.58°W., 33.7 ft., shows good face.

Set Brass cap at cor. mkd:

	County Surveyors Office	
R	T 30 S	R
1	¼ S 24	1
W	1968	E

New BT - 24" D.Fir N.85°W., 19.0 ft. mkd. ¼ S24 CS BT.
The sec. cor. of 18 & 19, T30S R1E lies 236 ft. North.