

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100437

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T30-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6682-83)

Set a basalt stone 15x8x8 ins., 10" in the ground for cor. of secs. 13 & 24, marked with 3 notches on N. and S. edges, from which

A Fir 12" dia., bears S.64°W., 30 lks. dist. mkd. T30S R1W S24 BT.

A Fir 30" dia., bears N.50°W., 38 lks. dist. mkd. T30S R1W S13 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6746)

The cor. of secs. 13 & 24 only, which is a basalt stone, 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone S24 on SW., and S13 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-86

Found - Stone at sec. cor., grooves on S E edge.
12" now 36" D.Fir S.58°W., 38.0 ft., shows good scar
30" now 46" D.Fir N.50°W., 25.1 ft., shows good scar
Record S.64°W., 19.8 ft., no trace of any tree at this point.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 30 S	R
1	<u>S 13</u>	S 18 1
W	S 24	E
	1968	

Trees in good condition and tagged. Did not tie between corners, too late.