

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6747)

-----  
Set an Iron post 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 18 only, with brass cap mkd. 1/4 S18  
1923

from which

A Fir 60" dia., bears N.62°E., 146 lks. dist. mkd. 1/4 S18 BT.

A Fir 30" dia., bears S.3°E., 124 lks. dist. mkd. 1/4 S18 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-87

-----  
Found - GLO brass cap at 1/4 cor., 1923, properly marked.  
60" now 60" D.Fir, N.58°E., (Rec. N.62°E.) 96.0 ft., shows good scar.  
30" now 36" D.Fir, S.3°E., 81.8 ft., shows good scar.

New BTs- 12" D.Fir S.73°E., 21.9 ft. mkd. 1/4 S18 CS BT.

10" D.Fir N.42°E., 27.2 ft. mkd. 1/4 S18 CS BT.

Did not tie between corners, too late in day.