

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only; T30-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6685)

Set a basalt stone 15x10x5 ins., 10" in ground for ¼ sec. corner marked ¼ on W. face, from which
A Fir 60" dia., bears SE., 26 lks. dist. mkd. ¼ S7 BT.
A Fir 14" dia., bears N.80°W., 57 lks. dist. mkd. ¼ S12 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6748)

The original ¼ sec. cor., which is a basalt stone, 12x5x5 ins. above ground, firmly set, marked ¼ on W. face. Hereafter, this cor. will refer to sec. 12 only. I mark the cor. stone ¼ S12 on W. face, from which
A Fir 12" dia., bears S.80°W., 56 lks. dist. mkd. ¼ S12 BT. (Old BT)
A Fir 26" dia., bears N.42°W., 57 lks. dist. mkd. ¼ S12 BT. (New BT)
I obliterate the marks on old BT in sec. 7.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-101

Found - Stone at ¼ corner, "¼" on West side.
Orig. 12" now 28" W. Fir S.80°W., 37.0 ft. scribe visible "¼ S12 BT".
26" D. Fir now stump, N.42°W., 37.6 ft. shows good scar. (New BT, 1923)
Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
1 ¼ S 12 | 1
W 1968 E
New BT - 18" Cedar N.74°W., 28.5 ft. mkd. ¼ S12 CS BT.
SW. BT OK and tagged.

Douglas Co. Surveyors Office - Gary Langlitz - Mike Tompkins - 9/16/1976 - C.S. File 59/24-13

Found - A stone, 24"x8"x6", firmly set, extending 8" above ground and leaning westerly, with faint "¼" chiseled on west face From which:
An orig. 1857 BT, a 15" now 34" D. Fir, alive with well healed blaze, bears N.10°W., 6.1 ft. (Rec. N.10°W., 5.2 ft.) continued next page

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100577

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only; T30-1W

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

An orig. 1857 BT, a 9" now 14" I.Cedar, alive with "BT" visible on unhealed blaze bears S.40°E., 7.1 ft. (Rec. S.40 6.6 ft.) Note: The markings on this tree were partially obliterated during the 1923 retracement survey.

A 1923 BT, a 12" now 20" I.Cedar bears S.35°W., 8.8 ft. (Rec. S.35°W., 9.9 ft.) Alive and well healed. Note: the orig. measurement fits this BT at breast height, not at ground level

At the corner point, we set:

A 1" x 30" I.P. - 24" in the ground with the orig. stone along the west side, stamped:

Douglas County Surveyor

T 30 S R 1 W

¼ S 12

1976

Note: This corner is located along the Willamette Meridian as surveyed in 1857 and later changed.