

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only; T30-1W

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6686)

-----

Set a basalt stone 15x14x5 ins., 10" in ground for ¼ sec. corner marked ¼ on W. face; from which

A Fir 24" dia., bears S.50°W., 54 lks. dist. mkd. ¼ S1 BT

A Fir 16" dia., bears S.45°E., 51 lks. dist. mkd. ¼ S6 BT

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #797 dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6133)

-----

Cor. is a basalt stone 5x12x5 ins. above ground, firmly set, and marked and witnessed as described by the Surveyor General. I re-establish this cor.in its original position as the ¼ sec. cor. on E. bdy. sec. 1, T30S R1W only, as follows: Stone already set and described, from which

A Fir 24" dia., bears S.30°W., 54 lks. dist. mkd. ¼ S1 BT

A Fir 40" dia., bears N.66°W., 43 lks. dist. mkd. ¼ S1 BT

I obliterate marks on former BT in T30S R1E.

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6749-50)

-----

The original ¼ sec. cor. changed by Deputy Mensch under contract #797 to refer sec. 1 only, which is a basalt stone 12x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone ¼ S1 on W. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Feb. 1968 - C.S. File 54/59-80

-----

Found - 40" D.Fir now stump, N.66°W., 28.4 ft., opened for scribe '¼".

24" D.Fir now stump, S.51°W., (Rec. S.30°W.) 35.6 ft.

Using 1 bearing and 2 distances, I renew: (No corner stone found)

Set brass cap at ¼ cor. mkd: County Surveyors Office

R		R
1	¼ S1	1
W	1968	E

(Cont. Next Page)

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 100677

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only; T30-01W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 22" Cedar S.57°W., 42.0 ft. mkd. ¼ S1 CS BT.  
          15" Laurel N.40°W., 34.2 ft. mkd. ¼ S1 CS BT.  
This corner lies in old skid road, running N-S. Township  
corner, (T29-1E & T30-1E) 266.4 ft. North.