

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 179700

PRIMARY CORNER DESCRIPTION Cor. Secs. 31 & 32 only, South: T29-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10569)

Set a basalt stone 15x10x8", 10" in the ground for cor. of secs. 5, 6, 31, & 32 mkd with 5 notches on E & 1 notch on W edges, from which

A madrone, 7" dia., bears N.6°E., 12 lks., mkd: T29S R1E S32 BT.

A fir, 24" dia., bears S.35°E., 37 lks mkd: T30S R1E S5 BT

A cedar, 7" dia. bears S.48°W., 44 lks mkd: T30S R1E S6 BT

A madrone, 12" dia., bears N.33°W., 19 lks., mkd: T29S R1E S31 BT.

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10986)

The corner established for secs. 5, 6, 31 & 32, which is a basalt stone, 10x8x5" above ground, firmly set, marked and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 31 & 32 only. I mark the cor. stone S 32 on NE & S 31 on NW face and obliterate the marks on old BTs S of line.

Douglas Co. Surveyors Office - A. Victor Cangie - M. Tompkins - P. Earle - Oct. 5, 1976 - C.S. File 59/24-23

Found - A 12x10x7" (rec. 15x10x8") stone with 5 notches on east face & 1 notch on west face as per record. I find no trace of "S32" on NE face or "S31" on NW face. I also find "GS" on south face & "X" chiseled on top both not of record.

The stone was disturbed & I re-establish proper location From:

A 7" now 11" Cedar bears S.50°W., (Rec. S.48°W.) 29.0 ft. I open & find old face with all but fragmentary scribe lines obliterated as per record. (when re-survey determined that above corner is not common to 4 sections but to 2)

An orig. 20" now 36" Fir, bears S.35°E., 24.4 ft. alive & well. Shows good scar.

I find no sign of any other BTs.

Set - A 1"x30" I.P. with brass cap stamped:

Douglas Co. Surveyor T 29 S R 1 E
1976 S31|S32

T 30 S R 1 E

continued next page

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 179700

PRIMARY CORNER DESCRIPTION Cor. Secs. 31 & 32 only, South: T29-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A 6" W.Fir, bears N.58°W., 20.7 ft. mkd. "T29S R1E
S31 CS BT" in a double blaze.
A 7" W.Fir, bears N.51½°E., 65.0 ft. mkd. "T29S R1E
S32 CS BT" in a double blaze.