

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11010)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T30S	R1E
S 19	S 20
S 30	S 29
1923	

from which

- A madrona, 7" dia., bears N.7°E., 22 lks., mkd: T30S R1E S20 BT.
- A fir, 32" dia., bears S.51°E., 34 lks., mkd: T30S R1E S29 BT.
- A fir, 18" dia., bears S.34°W., 57 lks., mkd: T30S R1E S30 BT.
- A cedar, 40" dia., bears N.33°W., 22 lks., mkd: T30S R1E S19 BT.