

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11016-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T30S	R1E
S 7	S 8
S 18	S 17

1923

from which

- A fir, 20" dia., bears N.26°E., 64 lks., mkd: T30S R1E S8 BT.
- A fir, 18" dia., bears S.59°E., 83 lks., mkd: T30S R1E S17 BT.
- A cedar, 20" dia., bears S.29°W., 101 lks., mkd: T30S R1E S18 BT.
- A B.Oak, 12" dia., bears N.3°W., 90 lks., mkd: T30S R1E S7 BT.