

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION CC Secs. 5 & 6, North

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10986)

-----  
Point of intersection of line bet. secs. 5 & 6, T30S R1E, determined as hereinafter set forth.  
Set a conglomerate stone 20x16x7", 15" in the ground for closing cor. of secs. 5 & 6 mkd with 5 grooves on E, CC and 6 grooves on S & 1 groove on W face, from which  
A fir, 16" dia., bears S.18°E., 33 lks., mkd: T30S R1E S5 CC BT.  
A fir, 14" dia., bears S.18°W., 27 lks., mkd: T30S R1E S6 CC BT.  
No iron post available for this corner.

Douglas Co. Surveyors Office - Gary Langlitz - K Cheney - Oct. 11, 1976 - C.S. File 59/24-29

-----  
Found - A conglomerate stone, firmly set, 18x14x7" (record 20x16x7") extending 10" above ground and supported in a mound of stone, with 5 grooves & a "5" & other illegible chisel marks on the east face, 1 groove & a "6" & other illegible chisel marks on the west face. We do not find any marks on the south face. From which:  
An orig. 16" now 20" D.Fir bears S.18°E., 21.8 ft. alive and well healed.  
An orig. 14" now 17" Grand Fir bears S.11°W., 17.8 ft. (rec. S.18°W) Alive and well healed.  
At the true location for the closing corner WE SET a 1"x30" I.P. 26" in ground & supported in a mound of stone, with brass cap attached stamped: Douglas Co. Surveyor T 29 S  
1976 S6 S5  
CC  
T 30 S  
We place the orig. stone along the south side of the brass cap and mark the following New BTs:  
A 12" Hemlock bears S.80°W., 18.7 ft. scribed "CC S6 T30S R1E CS BT" on a double blaze.