

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 5, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11196)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 32}{S\ 5}$
1923

from which

A fir, 24" dia., bears S.78°W., 58 lks., mkd: 1/4 S5 BT.

A fir, 40" dia., bears N.59°W., 27 lks., mkd: 1/4 S32 BT.

James N. Landrum USFS & Deputy Co. Surveyor - Leonard Herzstein - April 6, 1983 - C.S. File 62/10-18

Found - 2 ft. dia. mound of stone and 1" dia. iron post, 36" long, lying on the ground, with GLO 1923 brass cap marked "1/4 S32 S5 1923".

28" D.Fir snag, bears S.78°W., 38.3 ft. with scribe marks "1/4 S5 BT" visible on partially healed blaze.

42" D.Fir bears N.59°W., 17.8 ft. with fragmentary scribe marks visible on partially healed blaze.

Set - At mound of stone dug down to bedrock. Marked "X" in bedrock and reset IP 24" in 4 ft. dia., mound of stone. I stamp "Reset 1983 LS 2024" on brass cap. (5-18-83)

New BT - 6" I.Cedar, bears S.28°E., 43.3 ft. scribed "1/4 S5 BT" on single blaze.

Note - Corner is approx. 40 ft. west of N-S ridge line and 400 ft. west of USFS road #3114-600.