

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 279700

PRIMARY CORNER DESCRIPTION Cor. Secs. 32 & 33 only (South); T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page 10570 & Vol. 26 Page 10968)

Set a conglomerate stone 15x12x6", 10" in the ground for cor. of secs. 4, 5, 32, & 33 mkd with 4 notches on E & 2 notch(es) on W edges, from which
A fir, 20" dia. bears N.3°E., 25 lks. mkd: T29S R1E S33 BT
A sugar Pine, 8" dia., bears S.73°E., 33 lks., mkd: T30S R1E S4 BT.
A fir, 36" dia. bears S.11°W., 18 lks. mkd: T30S R1E S5 BT
A fir, 16" dia. bears N.89°W., 20 lks mkd: T29S R1E S32 BT

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10682 & Vol. 26 Page 10968)

The cor. established for secs. 4, 5, 32, & 33, which is a conglomerate stone, 12x6x5" above ground, firmly set, marked & witnessed as described by the surveyor general.
Here after this cor. will refer to secs. 32 & 33 only. I mark the stone S33 on the NE & S32 on NW face and obliterate the marks on the old BTs S of the line.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Sept. 1974 - C.S. File 57/8-2

Found - A conglomerate stone, firmly set, measuring 12x12x6" (rec. 15x12x6") mkd. with 2 notches on the W face
We find no additional markings on this stone.
An orig. 20" now 22" D.Fir, uprooted and down, bears N.3°E., 16.5 ft no marking fd orig face is buried
An orig. 16" D.Fir, now down and rotten, bears N.89°W., 13.2 ft. We find scribing "1I 32 B" on wood fragments in rotten stump hole.

We find two additional BTs marked by Mensch in 1910 for the corner of sections 32 & 33, 4 & 5 which were defaced by Mensch in 1923 when this corner was found to be common to sections 32 and 33 only.

At the corner point, we set a brass cap marked:

COUNTY SURVEYORS	T 29 S
OFFICE	S 32 S 33
1974	S 5
	T30S R1E

We place the orig. stone alongside and mark the following BTs
A 19" G.Fir, bears N.64°W., 43.4 ft. scribed "T29S R1E S32 CS BT"

continued next page

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 279700

PRIMARY CORNER DESCRIPTION Cor. Secs. 32 & 33 only (South); T30-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 14" I.Cedar, bears N.25½°E., 41.6 ft. scribed "T20S R1E
S33 CS BT".
Compass declination set at 20° East.