

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11003)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T30S	R1E
S 5	S 4
S 8	S 9
1923	

from which

- A fir, 17" dia., bears N.72°E., 17 lks., mkd: T30S R1E S4  
BT.
- A fir, 18" dia., bears S.83°E., 24 lks., mkd: T30S R1E S9  
BT.
- A fir, 24" dia., bears S.62°W., 40 lks., mkd: T30S R1E S8  
BT.
- A fir, 28" dia., bears N.57°W., 22 lks., mkd: T30S R1E S5  
BT.