

PRIMARY CORNER DESCRIPTION CC Secs. 4 & 5, North

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10682 & Vol. 26 Page(s) 10984-5)

-----  
Point of intersection of line bet. secs. 4 & 5, T30S R1E, determined as hereinafter set forth.  
Set a conglomerate stone 20x14x4", 15" in the ground for closing cor. of secs. 4, & 5 mkd with 4 grooves on E, CC & 6 grooves on S, and 2 grooves on W face, from which  
    A madrona, 18" dia., bears S.21°E., 22 lks., mkd: T30S R1E S4 CC BT.  
    A fir, 10" dia., bears S.47°W., 25 ft., mkd: T30S R1E S5 CC BT.  
No iron post available for this cor.

-----  
Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Sept. 5, 1974 - C.S. File 57/8-4

-----  
Found - A conglomerate stone, firmly set of which the exposed portion measures 14"x4"x6" with 4 grooves and "RIE S4" chiseled on the east face, "CC" chiseled on the south face and 2 grooves and "T30S" chiseled on the west face. From which:  
    An orig. 10" now 15" D.Fir, leaning badly bears S.47°W., 16.5 ft. alive and well healed.  
We find a small ground depression, but no other trace of the original SE bearing tree.  
We leave the orig. stone in place at the closing corner and following:  
New BTs- An 18" Sugar pine bears S.8°E., 24.7 ft. scribed "CC T30S R1E S4 CS BT".  
    A 10" Grand Fir bears S.85°W., 33.9 ft. scribed "CC T30S R1E S5 CS BT".  
Compass declination setting at 20° East.

-----  
Dennis Gaylord, USFS & DCSO Deputy - Walter Barton - May 26, 1977 - C.S. File 59/34-25

-----  
Found - Conglomerate stone 15x13x6", 5" above ground set solidly. marked "R1E S4" and 4 grooves on the East face, "CC" on the South face, "T30S S3" and 2 grooves on the West face.  
    Orig. D.Fir, 16" bears S.47°W., 16.5 ft. has healed blaze.  
    A 18" S.Pine bears S.8°E., 24.7 ft. scribing visible "CC T30S R1E S4 CS BT" on a double blaze.

continued next page

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION CC Secs. 4 & 5, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 11" G.Fir bears S.85°W., 33.9 ft. scribing visible on a double blaze, "CC T30S R1E S5 CS BT".

Set - Moving the orig. stone monument aside, I set in it's place a 2½" brass cap on a 1" Gal. I.P. stamped: County Surveyors Office T29S S33, S5 S4 T30S R1E CC 1977

I bury stone alongside. Place a 18x18x12" stone mound around brass cap.

No new BT's marked.