

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10681 & Vol. 26 Page 10984)

Point for the ¼ sec. cor. of sec. 4 only
Set a conglomerate stone 20x12x8" 15" in the ground, for ¼ sec. cor. of sec. 4 only, marked ¼ S4 on S face; from which
A fir, 20" dia., bears S.38°E., 37 lks., mkd: ¼ S4 BT.
A fir, 9" dia., bears S.80°W., 33 ft., mkd: ¼ S4 BT.
No iron post available for this corner.

Douglas Co. Surveyors Office - A. Victor Cangie - M. Tompkins
- Oct. 6, 1976 - C.S. File 59/24-24

Found - An orig. 20" now 24" Fir stump with healed blaze.
I open and find "S4" Tree bears S.38°E., 24.4 ft.
Found no trace of other BTs or corner stone.
Set - From above BT, I determine corner point and set: A
1"x30" I.P. brass cap stamped:
Douglas Co. Surveyor T29S R1E
1976 S 4
T30S R1E
New BTs- A 6" D.Fir, bears N.13°E., 54.3 ft. mkd. "¼ S CS BT"
in a double blaze.
A 17" D.Fir, bears S.9½°W., 102.4 ft. mkd. "¼ S4 CS
BT" in a double blaze.