

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3 & 4 T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 11194-5)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T30S	R1E
S 33	S 34
S 4	S 3
T31S	
1923	

from which

- A fir, 24" dia., bears N.65°E., 16 lks., mkd: T30S R1E S34 BT.
- A fir, 22" dia., bears S.63°E., 29 lks., mkd: T31S R1E S3 BT.
- A fir, 18" dia., bears S.3°W., 19 lks., mkd: T31S R1E S4 BT.
- A fir, 24" dia., bears N.37°W., 6 lks., mkd: T30S R1E S33 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept/Nov 1936 - (DCSO Vol. 46 Page(s) 17635)

The cor. of secs. 3, 4, 33, & 34, which is an iron post 2" dia., 9" above ground, firmly set, mkd. and witnessed as described in the official record.