

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10988)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 27, 28, 33, & 34, with brass cap mkd

T30S	R1E
S 28	S 27
S 33	S 34
1923	

from which

- A fir, 20" dia., bears N.15°E., 12 lks., mkd: T30S R1E S27 BT.
- A fir, 10" dia., bears S.14°E., 46 lks., mkd: T30S R1E S34 BT.
- A pine, 20" dia., bears S.30°W., 47 lks., mkd: T30S R1E S33 BT.
- A fir, 12" dia., bears N.11°W., 48 lks., mkd: T30S R1E S28 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14078)

Cor. of secs. 27, 28, 33, & 34, which is an iron post, 2" dia., 9" above ground firmly set, mkd. & witnessed as described in the official record.