

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10989)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T30S	R1E
S 21	S 22
S 28	S 27

1923

from which

- A fir, 16" dia., bears N.38°E., 22 lks., mkd: T30S R1E S22 BT.
- A fir, 24" dia., bears S.14°E., 23 lks., mkd: T30S R1E S27 BT.
- A fir, 30" dia., bears S.64°W., 11 lks., mkd: T30S R1E S28 BT.
- A yew, 12" dia., bears N.57°W., 60 lks., mkd: T30S R1E S21 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14080)

... Cor. of secs. 21, 22, 27, & 28, which is an iron post, 2" dia., 9" above ground, firmly set, mkd. & witnessed as described in the official record.