

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10990)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

T30S	R1E
S 16	S 15
S 21	S 22
1923	

from which

- A fir, 18" dia., bears N.29°E., 22 lks., mkd: T30S R1E S15  
BT.
- A fir, 16" dia., bears S.15°E., 26 lks., mkd: T30S R1E S22  
BT.
- A fir, 18" dia., bears S.83°W., 22 lks., mkd: T30S R1E S21  
BT.
- A fir, 12" dia., bears N.35°W., 7 lks., mkd: T30S R1E S16  
BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14082)

-----  
... cor. of secs. 15, 16, 21, & 22 which is an iron post, 2" above ground, firmly set, mkd. & witnessed as describes in the official record.