

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10991-2)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T30S		R1E
S 9		S 10
S 16		S 15
1923		

from which

- A hemlock, 14" dia., bears N.34°E., 84 lks., mkd: T30S R1E S10 BT.
- A fir, 16" dia., bears S.81°E., 11 lks., mkd: T30S R1E S15 BT.
- A fir, 28" dia., bears S.41°W., 50 lks., mkd: T30S R1E S16 BT.
- A hemlock, 24" dia., bears N.84°W., 53 lks., mkd: T30S R1E S9 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14084)

... cor of secs. 9, 10, 15, & 16, which is an iron post, 2" dia., 9" above ground, firmly set, mkd. and witnessed as described in the official record.