

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10992-3)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T30S	R1E
S 4	S 3
S 9	S 10
1923	

from which

- A pine, 30" dia., bears N.7°E., 24 lks., mkd: T30S R1E S3 BT.
- A cedar, 20" dia., bears S.30°E., 39 lks., mkd: T30S R1E S10 BT.
- A pine, 28" dia., bears S.57°W., 59 lks., mkd: T30S R1E S9 BT.
- A fir, 30" dia., bears N.19°W., 72 lks., mkd: T30S R1E S4 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14086-7)

... cor. of secs. 3, 4, 9 & 10, which is an iron post, 2" dia., 9" above ground, firmly set, (properly) mkd

from which

- A Y.Pine, 20" dia., bears N.8°E., 24 lks., blaze healed; I do not open (Old BT)
- An I.Cedar, 16" dia., bears S.30¼°E., 40 lks. blaze healed; I do not open (Old BT)
- A Y.Pine, 20" dia., bears S.57°W., 60 lks. blaze healed; I do not open. (Old BT)
- An I.Cedar, 22" dia., bears N.14°W., 132 lks. mkd. T30S R1E S4 BT. (New BT)