

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14080)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap mkd

T30S	R1E
S 22	S 23
S 27	S 26
1937	

from which

An I.Cedar, 30" dia., bears N.13¼°E., 28 lks., mkd: T30S R1E S23 BT.

A fir, 14" dia., bears S.66¼°E., 25 lks., mkd: T30S R1E S26 BT.

A fir, 20" dia., bears S.37°W., 68 lks., mkd: T30S R1E S27 BT.

An I.Cedar, 16" dia., bears N.81¼°W., 70 lks., mkd: T30S R1E S22 BT.