

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14083-4)

-----  
N.0°02'W., between secs. 14 & 15 at 39.76 chains  
Set an iron post, 3 ft. long, 1" dia., 6" in the ground to bedrock, and in a mound of stone to top, for witness cor. to the ¼ sec. cor., with brass cap mkd:

W C  
¼  
S 15|S 14  
1937

from which

A fir, 8" dia., bears N.10½°E., 48 lks., mkd: WC ¼ S14 BT.  
A hemlock, 14" dia. bears N.4°W., 10 lks. mkd: WC ¼ S15 BT  
40.00 chains - True point for ¼ sec. cor. falls on precipitous rock slope