

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35 only; T29-1E

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10573 & 10972)

Set a conglomerate stone 15x1x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 10" dia., bears N.53°E., 32 lks., mkd: ¼ S35 BT.
A fir, 6" dia., bears S.81°E., 22 lks., mkd: ¼ S2 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14075)

The orig. ¼ sec. cor. of secs. 2 & 35, which is a basalt stone, 15x9x4" firmly set, mkd. ¼ on N face. Hereafter this cor. will refer to sec. 35 only.
At point for corner,
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base, for the ¼ sec. cor. of sec 35 only, with brass cap marked:
¼ S 35
1937

from which
A fir, 15" dia., bears N.55°E., 32 lks., blaze healed; I do not open (Old BT)
A fir, 11" dia., bears S.81°E., 20 lks., mkd: ¼ S2 BT I obliterate the marks on this tree. (Old BT)
A fir, 11" dia., bears N.38°W., 56 lks., mkd: ¼ S35 BT. (New BT)

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton & Joel Sheriff - March 1977 - C.S. File 59/31-16

Found - 1937 GLO brass cap stamped U.S. General Land Office Survey 1/4 S35 1937. (T29S, R1E) Original corner stone alongside mkd. "X" on top
A 21" D.Fir bears N.55°E., 21.12 ft. Has a healed blaze.
A 17" D.Fir bears N.38°W., 37.7 ft. (Rec. N.38°W., 36.96 ft.) Has a healed scar.
A 17" D.Fir bears S.81°E., 13.2 ft. Has a healed scar.
All 3 BTs are alive & well. Placed County BT signs on all trees. DID NOT REMONUMENT CORNER.