

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 2 only;

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14103)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 2 only, with brass cap marked:

¼ S 2  
1937

from which

A pine, 14" dia., bears S.38°E., 48 lks., mkd: ¼ S2 BT.

A fir, 13" dia., bears S.6°W., 102 lks., mkd: ¼ S2 BT.

-----  
Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton & Joel Sheriff - March 1977 - C.S. File 59/31-15

-----  
Found - 1937 GLO brass cap properly stamped. (Did not show T & R.)

A 21" Ponderosa Pine bears S.38°E., 31.68 ft. Has a healed scar.

A 15" D.Fir bears S.6°W., 67.32 ft. Has a healed blaze.

Placed County BT signs on both trees which are alive and well. DID NOT REMONUMENT CORNER.