

PRIMARY CORNER DESCRIPTION South Cor. Secs. 35 & 36; only; T29-1E

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10574 & 10972)

-----  
Set a conglomerate stone 15x15x12", 10" in the ground for cor. of secs. 1, 2, 35, & 36 mkd with 1 notches on E & 5 notches on W edges, from which  
A pine, 28" dia., bears N.63°E., 27 lks., mkd: T29S R1E S36 BT.  
A fir, 24" dia., bears S.35°E., 44 lks., mkd: T30S R1E S1 BT.  
A fir, 20" dia., bears S.52°W., 20 lks., mkd: T30S R1E S20 BT.  
A pine, 30" dia., bears N.55°W., 77 lks., mkd: T29S R1E S35 BT.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14074)

-----  
The orig. cor. of secs. 1, 2, 35, & 36, which is a conglomerate stone 12x12x8", firmly set, mkd. with 1 notch on E & 5 notches on W edge. Hereafter this cor. will refer to secs. 35 & 35 only.  
At point for corner  
Set an iron post, 3 ft. long, 2" dia., 2" in the ground, with the orig. stone deposited at the base, for the cor. of secs. 35 & 36 only, with brass cap marked:  
T29S R1E  
S 35 | S 36  
T30S R1E  
S 2  
1937

from which  
A dead pine, 30" dia., bears N.65°E., 28 lks., mkd: T29S R1E S36 BT. (Old BT)  
A fir, 23" dia., bears S.32°E., 44 lks., mkd: T30S R1E S1 BT. I obliterate the marks on this tree (Old BT)  
A fir, 25" dia., bears S.50°W., 20 lks., mkd: T30S R1E S2 BT. I obliterate the marks on this tree (Old BT)  
A dead pine, 35" dia., bears N.56°W., 77 lks., mkd: T29S R1E S35 BT. (Old BT)  
A pine, 32" dia., bears N.43°E., 58 lks., mkd: T29S R1E S36 BT. (New BT)  
A cedar, 45" dia., bears N.18°W., 109 lks., mkd: T29S R1E S35 BT. (New BT)

continued next page

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 579700

PRIMARY CORNER DESCRIPTION South Cor. Secs. 35 & 36; only; T29-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton & Joel Sheriff - March 1977 - C.S. File 59/31-8

-----  
Found - 1937 GLO brass cap properly stamped. Is 6" above ground. Orig. cornerstone is alongside, with "X" on top.

A 52" Incense Cedar bears N.18°W., 71.94 ft. Has a healed blaze.

A 37" Ponderosa Pine bears N.43°E., 36.9 ft. Has a nearly healed blaze. Slope distance is 38.28 ft. Some scribing visible.

A 24" D.Fir bears S.32°E., 28.4 ft. Has a healed blaze.

A 28" D.Fir bears S.50°W., 14.5 ft. No scribing visible on open blaze. Tree is leaning badly.

A broken Pine stump bears N.56°W., 59.82 ft. scribing visible "T295 R1E S35 BT".

A decomposed stump bears N.67°30'E., 18.05 ft. No scribing visible.

Placed County BT signs on Cedar and Pine.  
DID NOT REMONUMENT CORNER.