

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14092)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 23, 24, 25, & 26 with brass cap mkd:

T30S	R1E
S 23	S 24
S 26	S 25
1937	

from which

- A fir, 15" dia., bears N.35°E., 119 lks., mkd: T30S R1E S24 BT.
- A fir, 13" dia., bears S.44°E., 11 lks., mkd: T30S R1E S25 BT.
- A fir, 25" dia., bears S.53°W., 65 lks., mkd: T30S R1E S26 BT.
- A fir, 38" dia., bears N.27°W., 54 lks., mkd: T30S R1E S23 BT.