

TOWNSHIP 30 RANGE 01E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14097)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

T30S	R1E
S 11	S 12
S 14	S 13
1937	

from which

- A fir, 15" dia., bears N.67°E., 53 lks., mkd: T30S R1E S12  
BT.
- A fir, 37" dia., bears S.42°E., 42 lks., mkd: T30S R1E S13  
BT.
- A fir, 15" dia., bears S.36°W., 59 lks., mkd: T30S R1E S14  
BT.
- A fir, 8" dia., bears N.26°W., 40 lks., mkd: T30S R1E S11  
BT.