

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6754)

A Fir 15" dia., cor. Ts. 30 & 31., R. 1 & 2 W., from which
A Fir 18" dia., bears S.70°W., 28 lks.
A Fir 15" dia., bears N.66°W., 121 lks.
A Fir 48" dia., bears N.48°E., 30 lks.
A Fir 15" dia., bears S.40°E., 20 lks.

Douglas Co. Surveyors Office - John M. Powell & crew - June 6, 1966 - C.S. File 54/28-7

Found - 15" Fir, now 36" Corner Tree, had been opened, scribing.
18" Fir now stump, S.70°W., 18.5 ft., shows good scar.
15" Fir now stump, N.66°W., 79.9 ft., shows scar.
48" Fir now 49" N.48°E., 19.8 ft., very old bark scribe.
15" Fir now 34" S.40°E., 13.2 ft., shows good scar
Set Brass cap at cor. mkd: County Surveyors Office

R	T30S	R
2	S 36	S 31
W	S 1	S 6
	1966	W

Brass cap set at NW. side of corner tree.
New BTs- 12" D.Fir N.19°W., 81.3 ft. scribed T30S R2W S36 CS BT.
11" D.Fir S.12°W., 109.3 ft. scribed T31S R2W S1 CS BT.
Corner lies on top of main ridge, running E. and W.