TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & S.25, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6650)

Marked a Fir 6" dia. for ¼ sec. corner, from which
A Fir 12" dia., bears S.40°W., 5 lks.
A Maple 12" dia., bears N.12°E., 16 lks.

Survey by Glenn Baughman - For: U.S. Forest Service (Umpqua National Forest) - July 1968 - C.S. File 55/83-6 and M 36-12

No evidence found of 1857 survey by Hathorn.
Set 2" x 30" I.P. with brass cap mkd:

R	T 30 S	R
2 ¼	S 25 | S 30	1
W	1968	W
	OLS 536	

New BTs- 48" dia. Cedar bears N.12°E., 22.5 ft. mkd. T30S R1W S30 BT.
12" dia. Fir bears S.38°W., 39.4 ft. mkd. T30S R2W S25 BT.
Placed USFS BT signs on both trees, breast high and facing pipe.

Survey by Glenn Baughman, LS #536 - For: U.S. Forest Service May 1978 - M 70-15

Found - 1968 brass cap set by Baughman and Ackaret.
48" Cedar stump bears N.12°E., 22.5 ft.
No BT in SW quadrant.
New BTs- 8" D.Fir bears S.9°W., 34.2 ft. scribed ¼ S25 BT.
9" D.Fir bears N.51°E., 51.0 ft. scribed ¼ S30 BT.

Gerald Nygren - For: Seneca Jones Timber Co. - Feb. 2015 - M169-12

Found - 1968 Brass cap per M36-12
48" Cedar stump bears N.12°E., 22.5'
16" D.Fir bears S.9°W., 34.2'
9" D.fir bears N.51°E., 51.0' (dead)
New BTs- 11" D.Fir bears S.89°W., 15.2', scribed "¼ S25 BT"
12" D.Fir bears N.13°E., 18.7' scribed "¼ S30 BT"