

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6650)

Set post corner secs. 19, 30, 24 and 25, from which
A Fir 50" dia., bears S.5°W., 25 lks.
A Fir 18" dia., bears S.55°E., 17 lks.
A Fir 20" dia., bears N.40°W., 19 lks.
A Fir 10" dia., bears N.70°E., 48 lks.

Survey by Glenn S. Baughman - For: U.S. Forest Service - July 1968 - C.S. File 55/83-5 and M 36-12

No evidence found of 1857 survey by Hathorn.

Set 2" x 30" I.P. with brass cap mkd:

R	T 30 S	R
2	S 24 S 19	1
W	S 25 S 30	W

1968
OLS 536

New BTs- 6" Chinquapin S.36°W., 23.5 ft. mkd. T30S R2W S25 BT.
6" W.Fir S.17°E., 46.0 ft. mkd. T30S R1W S30 BT.
24" D.Fir N.56°E., 22.4 ft. mkd. T30S R1W S19 BT.
8" Maple N.20°W., 6.2 ft. mkd. T30S R2W S24 BT.
Placed USFS BT sign on both trees, breast high and facing pipe.

Survey by Glenn Baughman - For: U.S. Forest Service - May 1978 - M 70-15

Found - 1968 brass cap set by Baughman and Ackaret.
8" Chinquapin bears S.36°W, 23.5 ft.
6" W.Fir bears S.23°E., 46.0 ft., down.
26" D.Fir bears N.56°E., 22.4 ft.
9" Maple bears N.20°W., 6.2 ft.
New BT - 10" D.Fir bears S.52°E., 69.4 ft. scribed T30S R1W S30 BT.