

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 12 only, T30-2

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6702)

Set a basalt stone 14x10x6 ins., 9½" in the ground for ¼ sec. cor. on E. bdy. sec. 12, marked ¼ on W. face, from which
 A Fir 10" dia., bears S.69°W., 27 lks. mkd. ¼ S12 BT.
 A W.Oak 5" dia., bears N.58°W., 48 lks. mkd. ¼ S12 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan. 1968 - C.S. File 54/59-39

Found - 10" now 18" D.Fir S.69°W., 17.8 ft., scribe visible "S12 BT"
 5" now 6" W.Oak N.58°W., 31.7 ft., shows good scar.
 Corner stone with "¼" on West face.
 Set Brass cap at cor. mkd: County Surveyors Office

R	T 30	S	R
2	S 12	¼	1
W			W

1968

Bearing trees OK., tagged same.
 This corner lies 33 ft. South of ¼ cor. sec. 7 only and on E-W cutting line.

Fd. OK, April 1995 by Nygren - M 121-76

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20333)

The original ¼ sec. cor. of sec. 12 only, on the E. bdy. of the Tp., perpetuated by Powell, in 1968, monumented with an iron pipe, 1¼" diam., firmly set, projecting 8" above a collar of stone, 3 ft. base, 8" to top, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 30	S	
R			R
2	S 12	¼	
W			W

1968

from which the remains of original bearing trees
 A fir, 25" diam., bears S.69°W., 27 lks., with a healed blaze.
 A roothole, bears N.58°W., 48 lks., with a down and decayed oak alongside, size indeterminate, with fragmentary reverse scribe marks visible.

continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100539

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 12 only, T30-2

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

and a new bearing tree

A fir, 8" diam. bears N.80 3/4°W., 75 lks., mkd. ¼ S12 BT.