

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6652)

Marked a Fir 18" dia., for 1/4 sec. corner, from which
 A Fir 18" dia., bears N.80°W., 38 lks.
 A Pine 12" dia., bears N.25°E., 35 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6702)

I re-establish the old 1/4 sec. corner in its original position as the 1/4 sec. corner on W. bdy. sec. 7, T30S R1W, as follows:
 The original corner, a Fir 30" dia., for 1/4 sec. corner, I mark 1/4 S7 on E. side, from which
 A Yellow Pine 18" dia., bears N.25°E., 36 lks. dist. mkd. 1/4 S7 BT.
 A B.Oak 8" dia., bears S.85°E., 31 lks. dist. mkd. 1/4 S7 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan. 1968 - C.S. File 54/59-38

Found - 30" now 36" corner tree, tree opened "S7" visible.
 8" now 12" B.Oak S.85°E., 20.5 ft., shows good scar.
 18" now 22" Pine N.7°E., (Rec. N.25°E.) 23.8 ft., shows good scar.

Set Brass cap on E. side of corner tree, mkd:
 County Surveyors Office
 R T30S R
 2 1/4 | S 7 1
 W | W
 1968

Bearing trees OK, tagged same.
 This corner lies 33.0 ft. North of 1/4 corner S. 12, T30-2.

Jim Landrum, U.S. Forest Service (Deputized by the County)
 Wit: L. Herzstein - June 16, 1983 - C.S. File 62/10-10

Found - Orig. 30" now 36" D.Fir corner tree with no scribe marks visible on previously opened blaze on West side and a healed blaze on East side.
 Orig. 22" P.Pine snag, N.7°E., 23.8 ft., with healed blaze.
 Orig. 12" B.Oak, S.85°E., 20.5 ft. with healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A reference monument, a 1¼" I.P. firmly set, projecting 6" above ground with brass cap, bears East 1.7 ft.

New Accessories:
I add "RM" above the date to the brass cap.
A 9" D.Fir N.50°E., 74.0 ft. scribed "¼ S7 CS BT" on a single blaze.
The ¼ corner of sec. 12 only, T30S R2W, bears South 33.0 ft.

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20334)