

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6652)

Marked a Fir 48" dia., for corner secs. 6, 7, 1 and 12, from which

- A Fir 12" dia., bears S.30°W., 40 lks.
- A Fir 30" dia., bears N.2°E., 80 lks.
- A Fir 12" dia., bears N.67°W., 172 lks.
- A Fir 24" dia., bears S.80°E., 100 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6703)

In its original position, I re-establish the old corner of secs. 1, 6, 7 and 12 as the corner of secs. 6 and 7, T30S R1W only, as follows:

Set a basalt stone 12x9x6 ins., 8" in the ground for corner of secs. 6 and 7, marked with 1 notch on N. and 5 notches on S. edge, from which

- A Fir 36" dia., bears N.2°E., 82 lks. dist. mkd. T30S R1W S6 BT.
- A Fir 30" dia., bears S.80°E., 100 lks. dist. mkd. T30S R1W S7 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan./Feb. 1968 - C.S. File 54/59-37

Found - Stone at section corner.
NE. BT, down and rotten.
30" now 39" D.Fir S.80°E., 66.0 ft., bark scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

R		T	30	S	R
2				S 6	1
W	S	1		S 7	W

1968

New BTs- 9" D.Fir S.71°E., 30.4 ft. mkd. T30S R1W S7 CS BT.
14" Cedar N.66°E., 35.1 ft. mkd. T30S R1W S6 CS BT.
This corner lies 50.8 ft. North of sec. cor. for 1, & 12, T30-2

continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20335-6)

The cor. of secs. 6 & 7 only, T. 30 S., R. 1 W., perpetuated by Powell, in 1968, monumented with an iron pipe, 1¼" diam., firmly set, projecting 2" above ground (alongside of which is the basalt stone, set by Mensch), with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
R S 6 R
2 S 1 ——— 1
W S 7 W
1968

from which the remaining bearing tree mkd. by Mensch
A fir, 42" diam., bears S.80 3/4°E., 102 lks. with fragmentary scribe marks visible on the bark. (Record, S.80°E., 100 lks.)
and the remains of bearing trees mkd. by Powell
A cedar snag, 14" diam., bears N.67 3/4°E., 53 lks., with a healed double blaze.
A fir, 12" diam., bears S.69 3/4°E., 45½ lks., with a healed double blaze.
and a new bearing tree
A cedar, 10" diam., bears N.24¼°E., 31½ lks., mkd. T30S R1W S6 BT.