

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6656

Set ¼ sec. post, from which
A hemlock, 10" dia., bears S.24°E., 5 lks.
A maple, 10" dia., bears N.40°E., 40 lks.

Douglas Co. Surveyors Office - John M. Powell - 2/1968 - C.S. File 54/59-72

Good blaze line - No trees found
Reported as not found.

Glenn Baughman - For: USFS, Tiller Ranger District - July 1968 - C.S. File 55/83-4, M36-11 & M36-12

No evidence found of 1857 survey by Hathorn
Set - 2x30" IP with brass cap mkd: T30S R1W
 ¼ S 19
 S 30
 1968
 OLS 536

New BTs- 14" Madrone, N.21°E., 27.3 ft mkd: ¼ S19 T30S R1W BT
 14" Pine, bears S.11°E., 17.0 ft. mkd: ¼ S30 T30S
 R1W BT.

Note - Placed USFS BT sign on both trees, breast high, facing pipe.

Douglas Co. Surveyors Office - Leonard Herzstein, Deputy & USFS - Witness: Art Arciniega & Joe Richey - Oct. 28, 1980 - C.S. File 61/11-34

Found - 2" IP firmly set, projecting 8" above ground with properly mkd brass cap set by Baughman in 1968.
A 14" madrone, south trunk of a triple clump, N.23½°E., 28.9 ft. (rec, N.21°E., 27.3 ft.) with scribe marks "¼ S19 T30S R1W BT" visible on partly healed blaze.
A 14" S.Pine snag, S.12¼°E., 17.3 ft. (Rec. S.11°E., 17.0 ft.) with scribe marks "¼ S30 T30S R1W BT" visible on partly healed blaze.

Set - Added 2 ft. mound of stone to corner monument.

New BT - 8" I.Cedar, S.25°E., 13.0 ft. scribed "¼ S30 CS BT"