

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 31, T29-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6059)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.88°W., 48 lks. dist.
A Fir 24" dia., bears N.70°W., 33 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Aug. 1, 1960 - C.S. File 51/121-1

Determined by old BTs:
30" Fir stump, logged, bears N.70°W., 21.8 ft.
30" Fir stump, logged, bears S.88°E., 31.8 ft.
At corner point, SET 1" x 30" Iron rod, from which
15" Sugar Pine S.15°W., 9.0 ft. mkd. ¼ S6 BT.
12" Fir bears N.75°W., 19.0 ft. mkd. ¼ S31 BT.
8" Fir bears N.4°E., 17.4 ft. mkd. ¼ S31 BT.
14" Alder bears S.67°E., 7.5 ft. mkd. ¼ S6 BT.

Survey by J.A. Hoffbuhr - For: Umpqua National Forest - July 2, 1970 - C.S. File 55/158 and M 40-4

Found - 1" dia. Iron rod.
Replaced rod with a 2" dia. Pipe with 2½" brass disk, stamped:
T 29 S R 1 W
¼ S 31
S 6
T 30 S R 1 W
R.L.S. 222
1970

from which bears
12" Fir N.4°E., 17.4 ft. shows good scar.
Orig. BT found, 30" stump, S.88°E., 31.8 ft.
14" Alder S.66°E., 7.2 ft. scribes visible.
21" Sugar Pine S.15°W., 8.7 ft.
14" Fir N.75°W., 18.6 ft.
Orig. BT found, 30" Fir stump, N.70°W., 21.8 ft.

BLM Resurvey by Donovan C. Harris, Cadastral Surveyor, under Group #748, Surveyed Aug. 1971 - (DCSO records Vol. 35 Page(s) 14583-84)

The ¼ sec. cor. of secs. 6 and 31, perpetuated and recorded by Markham in 1960, subsequently remonumented by Hoffbuhr in 1970, with an iron post 2½" dia., firmly set, extending 12" above ground with cap as marked in 1970, from which the remaining original bearing tree
(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 31, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir stump 30" dia., bears N.70°W., 33 lks. dist. mkd. with rotted face.
and bearing trees mkd. by Markham
A Fir 10" dia., bears N.2°E., 26 lks. dist. mkd. with healed blaze.
An Alder 14" dia., bears S.65°E., 11 lks. dist. with scribe marks $\frac{1}{4}$ S6 visible on partly healed blaze.
A Pine 22" dia., bears S.15 $\frac{1}{2}$ °W., 14 lks. dist. mkd. with healed blaze.
A Fir 16" dia., bears N.76°W., 29 lks. dist. mkd. with healed blaze.
A careful search was made for the $\frac{1}{4}$ sec. cor. established by F. Mensch. No evidence was found.
Cor. falls in a dense stand of timber and scattering undergrowth.

(Note: With material furnished me, I found no Mensch corner information for this $\frac{1}{4}$ corner.) V.Laugen, Aug. 1997

Fd. OK, Sept. 1993 by H. Pieske - M 117-62