

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6647)

-----  
 Set post corner secs. 31, 32, 5 and 6, from which  
 A Fir 10" dia., bears S.35°W., 14 lks.  
 A Fir 6" dia., bears S.28°E., 22 lks.  
 A Fir 18" dia., bears N.20°W., 23 lks.  
 A Fir 24" dia., bears N.2°E., 33 lks.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1966 - C.S. File 54/28-3

-----  
 Found - 10" Fir now 11", S.35°W., 9.2 ft., opened for scribe "6".  
 6" Fir now stump, S.28°E., 14.6 ft.  
 18" Fir now 27", N.20°W., 15.2 ft., bark scribed S31 BT scar.  
 24" Fir now stump, N.2°E., 21.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office  

T30S	R1W	S 31	S 32
T31S		S 6	S 5

 1966

New BTs- 11" D.Fir N.80°E., 40.8 ft. scribed T30S R1W S32 CS BT.  
 17" D.Fir S.52°E., 51.3 ft. scribed T31S R1W S5 CSBT  
 26" D.Fir S.72°W., 21.2 ft. scribed T31S R1W S6 CSBT

Glenn Baughman - For: U.S. Forest Service - July 1979 - C.S. File 58/176-36

-----  
 Found - A 1" I.P. projecting 16" above the ground with a 2½" brass cap mkd. by the DCSO.  
 11" D.Fir with partially healed blaze, bears S.35°W., 9.2 ft.  
 28" D.Fir wind thrown stump, bears N.20°W., 15.2 ft.  
 24" D.Fir stump, bears N.2°E., 21.8 ft.  
 12" D.Fir with healed blaze, bears N.80°E., 40.8 ft.  
 18" D.Fir with healed blaze, bears S.52°E., 51.3 ft.  
 26" D.Fir with scribe marks visible on a partially healed blaze, bears S.72°W., 21.2 ft.

New BT - A 16" W.Fir bears N.56°W., 140.1 ft. I marked "T30S R1W S31 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Loyd R. Moffit - For: U.S. Forest Service - Dec. 1986 - C.S.  
File 62/30-19

-----

Found - 1966 DCSO 2½" brass cap on 1" I.P.  
24" rotted Fir stump which bears N.02°E., 21.8 ft.  
12" Fir which bears N.80°E., 40.8 ft. scar visible.  
18" dead Fir which bears S.52°E., 51.3 ft., scribe  
visible.  
14" Fir which bears S.35°W., 9.2 ft. scar visible.  
20" dead Fir which bears S.72°W., 21.2 ft. scribe  
visible.  
16" Fir which bears N.56°W., 140.1 ft. scribe  
visible.  
27" uprooted Fir which bears N.20°W., 15.2 ft.  
24" Fir which bears N.89°W., 23.0 ft. scar visible.  
(Original unknown)  
New BT - 7" Cedar which bears S.40°E., 62.8 ft. from the  
corner, scribed "T31S R1W S5 BT" with LS washer  
No. 944 nailed to BT scribe.