

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6655  
-----

A fir, 4" dia., corner secs. 29, 30, 31, & 32, from which  
A laurel, 12" dia., bears S.30°E., 9 lks.  
A dogwood, 5" dia., bears S.10°W., 6 lks.  
A fir, 15" dia., bears N.46°W., 30 lks.  
A fir, 12" dia., bears N.20°E., 20 lks.

John Markham - For: Stomar Lbr. Co. - Oct. 31, 1960 - C.S. File 51/121-7  
-----

Sec. corner to secs. 29, 30, 31, & 32 as determined by OBT:  
20" Fir snag N.46°W. 19.8' OBT. I chopped out & fd scribe.  
25" Fir snag N.47°E., 13.2' OBT.  
At cor. pt. set 1"x36" IP  
From which  
14" W.Fir bears S.29°W., 8.7' mkd. XS31X BT.  
26" Fir S.6°W., 38.0' mkd. S31 R1W BT.  
32" W.Fir N.55°E., 31.7' mkd: S29 BT.  
14" Fir N.8°W., 96.0' mkd S30 BT.  
Road bears North 230.0'

Bruce Shaner - For: US Forest Service - Jan. 1981 - M79-72 & RM 3-43  
-----

Found - 1" I.P.  
20" D.Fir snag, orig. BT, scribes visible bears N.46°W., 19.8 ft.  
25" D.Fir stump, orig. BT partial face, bears N.47°E., 13.2 ft. (GLO rec. N.20°E; Markham rec. 1961, N.47°E.)  
22" W.Fir BT scribes visible bears S.29°W., 8.7 ft.  
30" D.Fir BT bark scribes visible bears S.6°W., 38.0 ft.  
32" W.Fir stump BT face visible bears N.55°E., 31.7 ft.  
16" D.Fir BT scribes visible bears N.8°W., 96.0 ft.  
Set - Brass cap in place of 1" IP mkd: "T30S R1W WM S29 S30 S31 S32 RLS 430, 1981"  
New BTs- 6" D.Fir BT, I scribed "T30S R1W S29 BT" bears N.74°E., 25.1 ft.  
6" D.Fir BT, I scribed "T30S, R1W S32 BT" bears S.68°E., 8.1 ft.

Fd. BC & Accessories by T. Hostetter, 4/2010 - M160-57