

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6656  
-----

Marked a fir 6" dia., for ¼ sec. post, from which  
A fir, 6" dia., bears N.10°E., 11 lks.  
A fir, 6" dia., bears S.50°W., 10 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-23  
-----

Found - Orig. 6" now 15" D.Fir N.10°E., 7.3 ft. opened for scribe "4S".  
No trace of 6" corner tree nor 6" SW BT.  
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T30S R1W OFFICE 1968 ¼ S30|S29  
Reblazed & rescribed -  
15" D.Fir N.10°E., 7.3 ft. scribed ¼ S29 CS BT.  
New BT - 28" D.Fir S.84°W., 14.4 ft. mkd. ¼ S30 CS BT.

Douglas Co. Surveyors Office - Leonard Herzstein, Deputy & USFS - Witness: Tom Wolford & Jim Landrum - April 1981 - C.S. File 61/19-43  
-----

Found - 1967 county brass cap, properly marked on 1" IP firmly set, projecting 12" above ground.  
Orig. 16" D.Fir snag, N.10°E., 7.3 ft. with scribe "4S" vis. on previously opened blaze & rescribed by Powell in 1967 with scribe "¼ S29 CS BT" visible on partly healed double blaze.  
A roothole, S.84°W., 14.4 ft. with 28" D.Fir stump alongside with no marks visible.  
I add 2 ft. dia., mound of stone with brass cap projecting 4" above.  
New BTs- 8" I.Cedar S.46°E., 17.0 ft. scribed "¼ S29 CS BT" on double blaze.  
5" I.Cedar S.56°W., 21.5 ft. scribed "¼ S30 CS BT" on double blaze.