

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6656  
-----

A fir 10, corner secs. 19, 20, 29, & 30, from which  
A fir, 9" dia., bears N.15°W., 31 lks.  
A fir, 12" dia., bears S.89°W., 12 lks.  
A fir 6" dia., bears S.47°E., 35 lks.  
A laurel, 12" dia., bears N.10°E., 23 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Feb. 1968 - C.S. File 54/59-68  
-----

Found - No trace of corner tree nor NW - NE BTs.  
6" D.Fir stob S.47°E., 23.1 ft. scribe visible "BT"  
12" D.Fir, now 20" dead S.89°W., 7.9 ft. opened for scribe.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W  
OFFICE S 19|S 20  
1968 S 30|S 29

New BTs- 6" D.Fir N.15°W., 28.8 ft. mkd: T30S R1W S19 CS BT.  
24" D.Fir N.15½°E. 26.5 ft. mkd: T30S R1W S20 CS BT.  
11" D.Fir S.33°E., 33.4 ft. mkd: T30S R1W S29 CS BT.  
35" D.Fir S.45°W., 44.9 ft. mkd: T30S R1W S30 CS BT.

Douglas Co. Surveyors Office - Leonard Herzstein, Deputy & USFS - Witness: Art Arciniega & Joe Richey - Oct. 30, 1980 - C.S. File 61/11-35  
-----

Found - 1968 County brass cap, properly marked on a 1½" IP firmly set, projecting 10" above ground.  
Orig. 22" D.Fir snag, S.89°W., 7.9 ft. to face with S.M. "BT" visible on previously opened blaze.  
A 24" D.Fir, N.15½°E., 26.5 ft. with partly healed blaze. 1968  
A 15" D.Fir, S.33°E., 32.3 ft. (Rec. 33.4 ft.) with healed doubled blaze. 1968  
A 35" D.Fir stump, S.45°W., 44.9 ft. with partly healed blaze.  
A 11" W.Fir, N.17°W., 29.3 ft. (Rec. D.Fir) bears N.15°W., 28.8 ft.) with partly healed blaze.

Set - Added 2 ft dia. mound of stone, IP now projecting 4"  
New BT - A 5" W.Fir, S.30¼°W., 31.4 ft. marked "T30S R1W S30 CS BT"