

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6656-7  
-----  
Set ¼ sec. post, from which  
    A laurel, 12" dia., bears N.5°E., 27 lks.  
    A fir, 8" dia., bears N.20°W., 16 lks.

Douglas Co. Surveyors Office - John M. Powell - 7/3/1968 - C.S. File 54/59-117  
-----  
Good N-S blazed line ¼ cor. is on edge of old cut unit, 2 small trees.  
Reported as not found.

Larry J. Friar - For: Umpqua National Forest - Feb. 1976 - M56-37  
-----  
Set - 2" pipe with 3" brass disk top properly stamped, from which:  
    A 12" fir bears S.88°35'E., 33.5 ft. scribed ¼ S20 BT.  
    A 8" fir, bears N.53°55'W., 13.5 ft. scribed ¼ S19 BT.

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, & Ignacio Roman - 6/2024 - C.S. File 65/112-9  
-----  
Found - 1976 Friar brass cap & iron pipe mkd as per M56-37  
        We place U-Post 1' north  
        20" D.Fir bears N.53°56'W., 13.5'. with BT tag and healed face. Record (N.53°55'W 13.5')  
New - 12" D.Fir bears N.3°W., 29.4'. We tag & scribe X BT  
      27" D.Fir bears S.9¾°W., 31.9'. We tag & scribe X BT  
      48" D.Fir bears S.27½°E., 191.6'. We tag & scribe ¼ S20 BT  
No other suitable trees within reasonable distance in sec. 20 BTs... were measured to an aluminum nail at the center face for angles ... and to an alum. nail at side center for distances... (Per narrative)