

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6657  
-----  
Set post corner secs. 17, 18, 19, & 20, from which  
A fir, 12" dia., bears S.5°W., 16 lks.  
A fir, 12" dia., bears S.7°E., 17 lks.  
A fir, 6" dia., bears N.20°W., 9 lks.  
A fir, 10" dia., bears N.70°E., 14 lks.

---

Douglas Co. Surveyors Office - John M. Powell - 7/3/1968 - C.S. File 54/59-117  
-----  
Reported as not found.  
Fd. 1 possible BT standing, old axe work, no scribing fd. Also possible BT down, out of place, old axe work no scribing, rotted out. Cruisers mks at approx. cor. N-S-E-W blazed lines.

---

Larry J. Friar - For: Umpqua National Forest - Feb. 1976 - M56-37  
-----  
Set - 2" pipe with 3" brass disk top properly stamped, from which:  
A 14" fir, bears N.78°05'E., 47.1 ft. scribed T30S R1W S17 BT.  
A 24" Pine bears S.21°31'E., 97.0 ft. scribed T30S R1W S20 BT.  
A 10" Fir, bears S.44°42'W., 97.1 ft. scribed T30S R1W S19 BT.  
A 10" Madrone, bears N.26°37' (W?) 28.8 ft. scribed T30S R1W S18 BT.

---

1