

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6658

Set post corner secs. 7, 8, 17, & 18, from which
A fir, 6" dia., bears S.2°E., 22 lks.
A fir, 5" dia., bears S.83°W., 20 lks.
A laurel, 6" dia., bears N.20°W., 35 lks.
A laurel, 6" dia., bears N.40°E., 25 lks.

Douglas Co. Surveyors Office - John M. Powell - June 1968 - C.S. File 54/59-88

Found - Corner stone, 15x10x8 mkd. with 4 grooves on S & 5 grooves on E.
9" now 14" D.Fir N.17°E., 23.8 ft. shows good scar.
10" now 16" D.Fir S.24°E., 23.1 ft. shows good scar.
12" now 18" D.Fir N.86°W., 15.2 ft. shows good scar.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE S 7 | S 8
1968 S 18 | S 17

Note - All BTs in good condition, did not mark new BTs.

William Ruppert, LS 866 - For: US Forest Service - April 1979 - M70-60

Found - 1" iron pipe with 2½" brass cap, 1968 County Surveyors Office
20" D.Fir, N.18°30'E., 23.1 ft. good scar.
19" D.Fir S.22°30'E., 21.6 ft. good scar
21" D.Fir, N.89°45'W., 14.9 ft. good scar.
21" D.Fir, S.4°30'W., 15.5 ft. good scar.
New BT - 9 D. Fir, S.74°00'E., 59.2 ft. "T30S R1W S17 BT"