

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6059)

Set post corner of secs. 31, 32, 5 and 6, from which
A Fir 10" dia., bears S.57°W., 38 lks. dist.
A Fir 15" dia., bears N.60°W., 36 lks. dist.
A Laurel 12" dia., bears S.74°E., 42 lks. dist.
A Chinquapin 8" dia., bears N.75°E., 27 lks. dist.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6067)

At the sec. cor., which is nearly obliterated. The old cor. which was a post, has disappeared and the Laurel and Chinquapin described as bearing trees in secs. 5 and 32 have fallen and decayed. The marks on the other bearing trees are nearly indistinguishable.

I destroy the old marks and re-establish the cor. in its original position as follows:

Set a basalt stone 15x12x6 ins., 10" in the ground for cor. of secs. 5, 6, 31 and 32, marked with 5 notches on E. and 1 notch on W. edge, from which

A Laurel 24" dia., bears N.88°E., 55 lks. dist. mkd. T29S R1W S32 BT.

A W.Fir 10" dia., bears S.38°E., 49 lks. dist. mkd. T30S R1W S5 BT.

A W.Fir 12" dia., bears S.56°W., 37 lks. dist. mkd. T30S R1W S6 BT.

A Red Fir 18" dia., bears N.61°W., 38 lks. dist. mkd. T29S R1W S31 BT.

(From this cor., J. Hurchinson's cabin bears N.45°W., about 5.00 chs. dist.)

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - Aug. 1, 1960 - C.S. File 51/121-2

Found - Orig. 22" W.Fir, S.38°E., 32.9 ft.
Orig., 30" Laurel bears N.88°E., 36.3 ft. I rescribed "S32 T29S R1W BT"

Orig. 24" Fir stump, logged, N.61°W., 25.1 ft.
At corner point, found stone and SET 1" x 30" I.P. from which
8" W.Oak bears N.85°W., 9.6 ft. mkd. S31 R1W BT.
10" W.Fir bears S.11°W., 19.3 ft. mkd. S6 R1W BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T29-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

J.A. Hoffbuhr, Umpqua National Forest - July 2, 1970 - C.S.
File 55/158 and M 40-4

Found 1¼" dia. Iron bolt. Also found original stone with 5
notches on West side.

Replaced 1¼" bolt with 2" dia. pipe with 2½" brass disk
stamped:

T 29 S R 1 W
S 31 | S 32
S 6 | S 5
T 30 S R 1 W
R.L.S. 222
1970

from which bears

Orig. BT, a 30" Madrona, blown down, N.88°E., 32.9 ft.

Orig. BT, a 22" W.Fir, blown down, S.38°E., 32.9 ft.

12" W.Fir scribes visible, S.11°W., 18.9 ft.

9" B.Oak BT, N.85°W., 9.6 ft.

Orig. BT, a 24" Fir, now a stump, logged off, N.61°W.,
25.1 ft.

Fd. and used Corner in BLM Resurvey by Donovan C. Harris,
Cadastral Surveyor, Group #748, Surveyed Aug. 1971 - (DCSO
records Vol. Vol. 35 Page(s) 14582-83)

Survey by Bruce A. Shaner - For: Umpqua National Forest -
Oct. 23, 1973 - M 49-43

Found - Brass cap mkd. in 1970.

15"x12"x6" Original stone and 1¼" x 27" iron bolt
alongside brass cap.

30" orig. Madrone, blown down, bears N.88°E., 32.9
ft.

22" orig. W.Fir, blown down, bears S.38°E., 32.9 ft.

24" orig. W.Fir, stup, bears N.61°W., 25.1 ft.

12" W.Fir scribes visible, bears S.11°W., 18.9 ft.

10" B.Oak scribes visible, bears N.85°W., 9.6 ft.

New BT - 6" D.Fir scribed "T29S R1W S32 BT", bears N.12½°E.,
45.8 ft. and nailed a brass washer to lower face.

Jim Landrum, U.S. Forest Service - (Deputized by DCSO) Wit:
Leonard Herzstein - June 9, 1983 - C.S. File 62/10-8

Found - 1970 brass cap, properly mkd. on a 2" I.P. firmly
set, projecting 8" above 2 ft. mound of stone.

Orig. stone set alongside with no marks visible.

1¼" Iron bolt, 27" long lays alongside.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. roothole, N.88°E., 36.3 ft. with 30" Madrone log alongside with a rotted blaze. (Rec. 32.9 ft.)
Orig., a roothole, S.38°E., 32.9 ft. with 22" W.Fir log alongside with a rooted blaze.
Orig. 34" D.Fir stump, N.61°W., 25.6 ft. (Rec. 25.1 ft.) with healed double blaze.
1960 BT, 16" W.Fir S.11°W., 18.9 ft. with healed double blaze.
1960 BT, 10" B.Oak N.85°W., 9.6 ft. with healed blaze.
1973 BT, 10" D.Fir N.12½°E., 45.8 ft. with healed double blaze.
New BT - 5" D.Fir S.56°E., 31.0 ft. scribed "T30S R1W S5 CS BT" on a single blaze.
Corner is about 100 ft. North of small creek and about 350 ft. South of USFS Road #2810

Fd. OK, Sept. 1993 by H. Pieske - M 117-62

Russell Badgley - For: USDA Forest Service - 7/2021 - M179-77

Found - A 2" iron post by Hoffbuhr, in 1970 per C.S. 55/158 and M 40-4, firmly set, projecting 3" above the ground with a 2½" brass cap (properly) mkd:
From which an original BT by Mensch in 1904:
A rotten D.Fir stump bears N.60°15'W., 25.9 ft (N.61°W., 25.6 ft) w/scribe partially visible
And BTs by Markham in 1960:
A 11" B.Oak bears N.84°45'W , 9.4 (N.85°W., 9.6 ft) w/healed double blaze
A 17" W.Fir S.10°30'W., 19.0 ft (S.11°W., 18.9 ft) w/healed double blaze & "X"
And a BT by Shaner in 1971
A 17" D.Fir N.12°E., 45.5 ft. (N.12½°E., 45.8 ft.) w/healed double blaze
and a BT by Landrum in 1983
A 14" D.Fir bears S.56°E., 30.9 ft. (S.56°W., 31.0 ft.) w/healed single blaze.
NAD83(2011)
Lat: 43°00'16.79838"N Long: 122°51'45.67925"W