

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - W.F. Briggs, County Surveyor -  
March 13, 1889 - Vol. 1 Pg 130

-----  
Set corner by marking: Fir 8" dia., on four sides  $\frac{1}{4}$ S, gave  
sight line East.

Tony Hostetter - For: Seneca Jones Timber Co. Co. - April  
2010 - M160-57

-----  
Set - 5/8"x36" rebar w/alum. cap mkd: "C $\frac{1}{4}$  S32 LS 1975 2010"  
from which  
9" Oak, scribed "S32  $\frac{1}{4}$  BT", bears N.37°E., 20.2 ft. to  
spike.  
9" W.Fir, scribed "S32  $\frac{1}{4}$  BT", bears N.74°E., 12.1 ft.  
to spike.  
12" Fir, scribed "S32  $\frac{1}{4}$  BT", bears S.02°W., 13.1 ft. to  
spike.  
15" W.Fir, scribed "S32  $\frac{1}{4}$  BT", bears S.57°W., 1.7 ft.  
to spike.