

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6664

Set ¼ sec. post, from which
A fir, 6" dia., bears N.5°E., 15 lks.
A fir, 18" dia., bears S.36°E., 25 lks.

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6693)

Set an ironstone 14x9x5", 9½" in the ground for ¼ sec. corner, marked ¼ on N face; from which
A R.Fir, 24" dia., bears N.74°E., 29 lks., mkd: ¼ S8 BT.
A R.Fir, 20" dia., bears S.40°W., 57 lks., mkd: ¼ S17 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-89

Found - Corner stone 14x9x5 mkd. "¼"
24" now 32" D.Fir N.74°E., 19.1 ft. shows good scar.
20" now 21" D.Fir stob, S.40°W., 37.6 ft. shows scribing "¼ S17"

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE ¼ S 8
1968 S 17

New BT - 10" D.Fir S.37°E., 28.6 ft. mkd: "¼ S17 CS BT"